



Material data sheet

Product Heavy Duty filmic labels,-white
2297

Facematerial	
Material description	White, heat stabilized, matt coated polyester film with toner receptive top coat.
Hardware suitability	A4 sheets for colour- and monochrome laser printer, monochrome copier -
Caliper	50 µm
Weight	75 g/m ²
Adhesive	
Type	<ul style="list-style-type: none"> ◆ clear permanent adhesive featuring excellent initial tack, adhesion,. ◆ Acrylic dispersion ◆ Solvent free
Peel performance	◆ Permanent
Coating weight	◆ 23 g/m ²
Properties	<ul style="list-style-type: none"> ◆ "wet-out" performance even on apolar surfaces such as HDPE. ◆ Improved temperature water, solvent and chemical resistance
Liner	
Material description	Hygroflat 100, a one side silicon coated, bleached kraft paper
Caliper	• 108 µm
Weight	• 98 g/m ²
Laminate	
Caliper	181 µm
Weight	196 g/m ²
Important properties (face and adhesive)	<ul style="list-style-type: none"> • Weatherproof • Sea water proofed according BS5609 • Waterproof • Good UV-stability • Oil resistant
Min. application temperature	0 °C
Service temperature	-20 °C – +80 °C no negative influence with a short-time higher temperature e.g. during printing on a laserprinter
Shelf life	Two years when stored at 20°C / 50% RH.

N.B. : All data to be considered as typical values